



HEMPEL'S WAX TecCel™ 69034

Description:	HEMPEL'S WAX TecCel 69034 is a high performance liquid wax with TecCel technology providing a long lasting, deep gloss finish with excellent protection. TecCel is the mark of HEMPEL'S advanced performance coatings, containing polytetrafluorethylene, giving significant improvements in performance.
Recommended use:	For use on gelcoat, painted and varnished surfaces after polishing with HEMPEL'S CUSTOM MARINE POLISH 67444. Leaves an easy to clean, water repellent surface with long-lasting protection. Suitable for both manual and machine use.
Availability:	Part of European Yacht assortment. Local availability subject to confirmation.
PHYSICAL CONSTANTS:	
Shade nos/Colours:	09990/ Off-white.
Flash point:	80 °C [176 °F]
Specific gravity:	1 kg/litre [8 lbs/US gallon]
pH:	8.3
VOC content:	217 g/l [1.8 lbs/US gallon]
	<i>The physical constants stated are nominal data according to the HEMPEL Group's approved formulas.</i>
APPLICATION DETAILS:	
Safety:	Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult HEMPEL Safety Data Sheets and follow all local or national safety regulations.
SURFACE PREPARATION:	Clean and degrease the surface with HEMPEL'S PRE-CLEAN 67062 or HEMPEL'S BOAT SHAMPOO 67284 to remove dirt and other contaminants, rinse with fresh water. Allow the surface to dry. Surfaces in good condition: Polishing with:HEMPEL'S CUSTOM MARINE POLISH 67444. Apply:HEMPEL'S WAX TecCel 69034. Deteriorated surfaces: Use:HEMPEL'S RUBBING LIQUID 69021 to restore and renew gloss and colour of gelcoat and painted surfaces followed by:HEMPEL'S CUSTOM MARINE POLISH 67444. Apply:HEMPEL'S WAX TecCel 69034.
APPLICATION CONDITIONS:	Shake well before use. Apply the product in a thin layer with clean, soft rags. Treat only small areas at a time. Allow the surface to dry. Polish using a clean, soft cloth or a polishing machine to obtain a more effective performance. Change to clean cloths frequently. Use a new, clean polishing pad when using the polishing machine.
SUBSEQUENT COAT:	None. To maintain the high gloss performance, apply extra layers when first signs of gloss decrease are observed.
REMARKS:	Do not apply in direct sunlight. The temperature should not be below: 5°C/41°F Allow freshly painted surfaces to dry/cure for at least 90 days before applying the product. Later if repainting is required, it is very important to remove all traces of wax by using: HEMPEL'S PRE-CLEAN 67602. Rinse the surface with fresh water.
Note:	HEMPEL'S WAX TecCel™ 69034 6903409990
ISSUED BY:	HEMPEL A/S

This Product Data Sheet supersedes those previously issued.

For explanations, definitions and scope, see "Explanatory Notes" available on www.hempel.com. Data, specifications, directions and recommendations given in this data sheet represent only test results or experience obtained under controlled or specially defined circumstances. Their accuracy, completeness or appropriateness under the actual conditions of any intended use of the Products herein must be determined exclusively by the Buyer and/or User.

The Products are supplied and all technical assistance is given subject to HEMPEL'S GENERAL CONDITIONS OF SALES, DELIVERY AND SERVICE, unless otherwise expressly agreed in writing. The Manufacturer and Seller disclaim, and Buyer and/or User waive all claims involving, any liability, including but not limited to negligence, except as expressed in said GENERAL CONDITIONS for all results, injury or direct or consequential losses or damages arising from the use of the Products as recommended above, on the overleaf or otherwise. Product data are subject to change without notice and become void five years from the date of issue.